



Firmware Release Note

Prestige 650R-11

Release 3.40(ES.4)C0

Date: Nov 21, 2002
Author: Chi-Wen Chen

ZyXEL Prestige 650R-11 Standard Version release 3.40(ES.4)C0 Release Note

Date: Nov 21, 2002

Supported Platforms:

ZyXEL Prestige 650R-11

Versions:

ZyNOS F/W Version: V3.40(ES.4) | 11/21/2002 11:05:29

Bootbase Version: V1.06 | 9/3/2002 11:07:17

Notes:

1. The Prestige 650 is a compact ADSL over POTS router that can be used for small-office or home-user and allows a small LAN to access the Internet through ADSL connection over the existing copper line.
 - Support Multi-Mode standard (ANSI T1.413, Issue 2; G.dmt(G.992.1); G.lite(G992.2)).
 - One auto-sensing 10/100M Ethernet interface
 - support Multi-protocol over AAL5 (RFC1483)
 - Support PPP over ATM AAL5 (RFC 2364)
 - Support PPP over Ethernet (RFC2516)
 - Support up to 8 PVCs
 - IP routing and bridging modes
 - Multi-NAT for Multi Global IP address Internet Access
 - DHCP Client, Sever and Relay
 - RIP I/ RIP II supported.
 - IGMP
 - IP alias
 - IP Policy Routing
 - ICMP Router Discovery
 - TFTP/FTP server for firmware upgrade
 - F4/F5 OAM
 - Call Scheduling for PPPoE
 - Support Web Configurator
 - Support Traffic Redirect
 - Support UPNP
2. For PPPoE, system must turn off the PPP VJ header compression. The command is as following:
“ppp ipcp compress off”, this command is already added into “autoexec.net”
3. Alcatel modem code version is 3.8.163 now.

Known Issues:

None

CI Command List:

Features:

Modification in V3.40(ES.4) | 11/21/2002

1. [FEATURE CHANGED] Change name for formal Release.

Modification in V3.40(ES.4)b3 | 11/6/2002

1. [BUG FIXED]
Sympton: SNMP get ADSL Modem Code version Error
Condition: The shown message at SNMP for ADSL modem code is error.
2. [BUG FIXED]
Sympton: SNMP get sysObjectID error.
Condition: The declaration about sysObjectID is error.

Modification in V3.40(ES.4)b2 | 10/16/2002

1. [FEATURE ENHANCED] Add UPNP Web Help.
2. [FEATURE ENHANCED] Add Traffic Redirect Web Help.
3. [BUG FIXED]
Sympton: Nailed-up don't work sometimes. Especially P652R11 with P1600.
Condition: Sometimes PPPoA couldn't connect with DSLAM.
4. [BUG FIXED]
Sympton: FTP server setting at NAT server set non-default rule would impact RemoteMagment.
Condition: RemoteMagment would be failed for FTP when the NAT server set had FTP port transfer at non-default rule.
5. [BUG FIXED]
Sympton: "IP Address" would become required field when the "IP Address Assignment" is dynamic at smt4.
Condition: This is only occurred when the encap is PPPoA / Dynamic changed to PPPoE / Dynamic.
6. [BUG FIXED]
Sympton: DDNS would not work at 1483 encapsultion.
Condition: Change the ip setting for the RFC1483 remoteNode. The ddns would not change the ip address for this domain name.
7. [BUG FIXED]
Sympton: when change Enet-Encap from static to dynamic by smt4, the add route routine would cause error record at "sys log disp".
Condition: Add redundant routing entry and this would cause the error record.

Modification in V3.40(ES.4)b1 | 9/4/2002

1. [FEATURE ENHANCED] Add UPNP Feature.
2. [FEATURE ENHANCED] Add Traffic Redirection Feature (detection by ADSL Line)

Modification in V3.40(ES.3) | 9/4/2002

1. [FEATURE CHANGED] Change name for formal Release.

Modification in V3.40(ES.3)b1 | 8/27/2002

1. [BUG FIXED]
Sympton: System reboot if change standard session to console from telnet under "sys log disp".
Condition: Under "sys log disp" mode, there are some characters still in the telnet session and this would cause the change error.

Modification in V3.40(ES.2) | 8/19/2002

1. [FEATURE CHANGED] Change name for formal Release.

Modification in V3.40(ES.2)b2 | 8/8/2002

1. [FEATURE ENHANCED] Add "Nail-Up" and "Password" configuration by sptgen
2. [FEATURE ENHANCED] Enlarge PPPoE username length to 70 chars
Note: So this version need to upgrade new rom-file
3. [FEATURE CHANGED] Change "PPP" to "PPPoA" at smt4/smt11/web
4. [FEATURE CHANGED] Change the rom-file setting for Switzerland version.
5. [BUG FIXED] Fix the configuration length about PPPoE idle timeout at web wizard

Modification in V3.40(ES.2)b1 | 7/25/2002

1. [FEATURE ENHANCED] Add "ADJUST_GAIN" commands to tune ADSL txGain and Target Noise.
2. [FEATURE ENHANCED] Add "wan adsl rsploss" ci-command
3. [FEATURE ENHANCED] Change the showing model name at smt main from "Prestige 650" to "Prestige 650R-11."
4. [BUG FIXED] Fix the ERROR PACKET trad parse for PPPoE packet.
5. [BUG FIXED] Fix the exception caused by the adsl line plug in and plug out.
6. [BUG FIXED] Fix dyingGasp occurred before loading modem code would cause system reboot.
7. [BUG FIXED] Fix the mbuf->flags would be impacted by hwsar vc number.
8. [BUG FIXED] Fix the smt save quickly would casue the system hang-up.
9. [BUG FIXED] Fix the atm discard packet would casue the exception.

Modification in V3.40(ES.0) | 6/17/2002

1. [FEATURE CHANGED] Change name for formal release.

Modification in V3.40(ES.0)b17 | 6/12/2002

1. [BUG FIXED] Fix ppp channel setting serval times by changing static and dynamic would cause system could not ping out.
2. [BUG FIXED] Fix oam F4 / F5 loopback test would be failure when debug flag is turned off.

Modification in V3.40(ES.0)b16 | 6/7/2002

1. [BUG FIXED] Fix the ip checksum error if the options existed in ip header.
2. [BUG FIXED] Fix the system hangup if the icmp echo request pass through our router in which the port translation setting in serverSet Table was from 1 to 2000.
3. [BUG FIXED] Fix the system hangup due to press left button in smt submenu 24.2 / 24.3 / 24.4 / 12 / 12.1 / 12.3.
4. [BUG FIXED] Fix the CPU Bus timeout if OAM packet pass through our router in which there is no such VC.
5. [BUG FIXED] Fix the channel drop fail and ring up fail problem at smt4/ smt11 (connection magnment)
6. [BUG FIXED] Fix the security webpage filter link list problem.

Modification in V3.40(ES.0)b15 | 5/28/2002

1. [FEATURE ENHANCED] Enlarge the adsl download modem code timing from 100ms to 200ms (HTP)
2. [FEATURE ENHANCED] Change rom-file setting for new structure.
3. [BUG FIXED] Fix the web-page cause the line drop if the setting is as before.
4. [BUG FIXED] Fix the NetBIOS packet incoming from Wan would cause our router exception.
5. [BUG FIXED] Fix the enet-encap could not bind wanip if the dsl line drop and link again.

Modification in V3.40(ES.0)b14 | 5/17/2002

1. [FEATURE ENHANCED] Change Bootbase to 1.04 version
2. [FEATURE ENHANCED] Merge SNMP trap v2
3. [FEATURE ENHANCED] Merge the new exception handler.
4. [BUG FIXED] Fix the DSL Active light is sparkling when no traffic pass through.
5. [BUG FIXED] Fix the exception when typing "sys iface disp wanif0 4" (after wanif0 had created)
6. [BUG FIXED] Fix the exception when new mac address pass through after the following setting steps: bridge is not set at smt1 and change bridge to router at smt11.
7. [BUG FIXED] Fix the exception if change the encap from PPP to 1483.
8. [BUG FIXED] Fix the PPP always idle if packet trigger before DSL line is up.
9. [BUG FIXED] Fix the default setting is lost when we clear the remoteNode by typing space at smt.
10. [BUG FIXED] Fix the username would be "?" if enter IP/Bridge option in smt11_01

Modification in V3.40(ES.0)b13 | 4/29/2002

1. [FEATURE ENHANCED] Add protection for null pointer to avoid exception.
2. [BUG FIXED] Modify the default dhcp pool number at Web from 4 to 32.

Modification in V3.40(ES.0)b12 | 4/22/2002

1. [BUG FIXED] Modify system reboot: telnet will sometimes let system reboot(exception occur.)
2. [BUG FIXED] Common Bug fixed(porting from IP department by slchiang): add system sometimes will point to null point , new rascode will to detect pointer is null or not.

Modification in V3.40(ES.0)b11 | 4/12/2002

1. [FEATURE ENHANCED] Unify the ADSL driver API for Web, Smt and ci-command.
2. [FEATURE ENHANCED] Add DyingGasp Recovery mechanism
3. [FEATURE CHANGED] Modify the console task priority.
4. [FEATURE ENHANCED] Add setting protection for MBS, Idle-timeout at smt4 / smt11. (0~65535)
5. [FEATURE ENHANCED] Support PPP packet trigger [Note: Now PPP bcp mode would not support]
6. [FEATURE ENHANCED] Add call filter at smt11.5 when the encap was packet trigger (PPPoE / PPP)
7. [FEATURE ENHANCED] Modify the default DHCP ip pool to 32, and change the name of smt3.1 / smt 3.2
8. [FEATURE ENHANCED] Enlarge the Queue number to 128, the tftp memory allocation size and the NatSessions (256 ->1024)
9. [FEATURE ENHANCED] Upgrade romPager(Web Engine) from 3.0 to 4.0
10. [BUG FIXED] Fix the larger packet ping failure from the Wan side at PPPoE encap.
11. [BUG FIXED] Fix the time couldn't be update from time server when the router reset or from the Lan side.
12. [BUG FIXED] Fix the wanIp would not be changed when changing the wanip from static to dynamic.
13. [BUG FIXED] Fix the system hang-up if pressing any key when loading ADSL modem code.
14. [BUG FIXED] Fix the enet-Encap setting would be failure by smt11_0l (not smt4)

Modification in V3.40(ES.0)b10 | 2/5/2002

1. [FEATURE ENHANCED] Support Dynamic DNS, it can be configured from SMT 1.1
2. [FEATURE ENHANCED] Support Remote Management, it can be configured from SMT 24.11
3. [FEATURE CHANGED] Alcatel modem code is upgraded to 3.8.163
4. [BUG FIXED] In Web system status, the subnet mask of remote IP address is wrong
5. [BUG FIXED] In Web "Show Statistics" display error in IE5

Modification in V3.40(ES.0)b9 | 12/17/2001

1. [BUG FIXED] Configured 4 remote nodes, when ADSL line is link down, some remote nodes are not really closed, after line links up.
2. [BUG FIXED] Configured 4 remote nodes, when ADSL line is link down, some remote nodes are not really closed, after line links up again, some remote nodes can't work

Modification in V3.40(ES.0)b8 | 12/4/2001

1. [BUG FIXED] System hangs-up when configured in bridge mode.
2. [BUG FIXED] System hangs-up when PPPoE mode is triggered.
3. [BUG FIXED] WAN iface will increase when system is configuring SMT4 - PPPoE or PPP again and again.

Modification in V3.40(ES.0)b7 | 11/20/2001

1. [FEATURE ENHANCED] support reset button to restore default ROM file.

2. [BUG FIXED] Using MIB browser to get all MIB will make system hang
3. [BUG FIXED] System can't support 1k-Xmodem to upload F/W through Procomm Plus
4. [BUG FIXED] System hang-up, when configuring remote nodes
5. [BUG FIXED] In testing Upstream stress test to 4 remote nodes, 4 remote nodes receive different packet counts
6. [BUG FIXED] In Web/GUI, system can't display DSL modem version
7. [BUG FIXED] Configure LAN port to 100Mbps but it is treated as 10Mbps

Modification in V3.40(ES.0)b6 | 11/8/2001

1. [FEATURE ENHANCEMENT] supports MIB-II.
2. [BUG FIXED] Change UBR to CBR, system will fail to ping.
3. [BUG FIXED] System will hang when using SNMP browser.
4. [Modem code] The modem code version name should be Alcatel 3.8.124
5. [BUG FIXED] system log can not be cleared
6. [BUG FIXED] Budget allocation can only be used when encapsulation is "PPPoE"

Modification in V3.40(ES.0)b5 | 10/26/2001

1. [FEATURE ENHANCED] Supports Embedded Web Configurator.
2. [FEATURE ENHANCED] Supports Uart using internal clock, but the baud rate only supports max to 38400bps
3. [FEATURE ENHANCED] change default VPI/VCI to 8/35.

Modification in V3.40(ES.0)b4

1. [FEATURE ENHANCED] Modify BOOTBASE and also BOOTEXT to support MX flash

Modification in V3.40(ES.0)b3

1. [FEATURE ENHANCED] In ATM RX.C ATM RX ISR, when receives error packets should free receive Rx count
2. [BUG FIXED] In SMT 3.2, DHCP item can't be saved.
3. [BUG FIXED] In SMT 11, the subnet mask of Remote IP address can't be saved.
4. [BUG FIXED] Throughput test by Smart Application will fail when test duration is 60 seconds or more

CI Command List

Command Class List Table		
System Related Command	Exit Command	Ethernet Related Command
Wan Related Command	IP Related Command	Bridge Related Command

System Related Command

[home](#)

Command				Description
sys				
	adjtime			retrive date and time from Internet
	atsh			display MRD field
			display	display cbuf static
	callhist			
		display		display call history
		remove	<index>	remove entry from call history
	countrycode		[countrycode]	set country code
	date		[year month date]	set/display date
	domainname			display domain name
	edit		<filename>	edit a text file
	extraphnum			maintain extra phone numbers for outcalls
		add	<set 1-3> <1st phone num> [2nd phone num]	add extra phone numbers
		display		display extra phone numbers
		node	<num>	set all extend phone number to remote node <num>
		remove	<set 1-3>	remove extra phone numbers
		reset		reset flag and mask
	feature			display feature bit
	hostname		[hostname]	display system hostname
	log			
		clear		clear log error
		disp		display log error
		online	[on off]	turn on/off error log online display
		link	link	list system mbuf link
		pool	<id> [type]	list system mbuf pool
		status		display system mbuf status
		disp	<address>	display mbuf status
	stdio		[second]	change terminal timeout value
	time		[hour [min [sec]]]	display/set system time
	trcdisp	parse, brief,		monitor packets

		disp		
	trclog			
	trcpacket			
	syslog			
		server	[destIP]	set syslog server IP address
		facility	<FacilityNo>	set syslog facility
		type	[type]	set/display syslog type flag
		mode	[on off]	set syslog mode
	version			display RAS code and driver version
	view		<filename>	view a text file
	wdog			
		switch	[on off]	set on/off wdog
		cnt	[value]	display watchdog counts value: 0-34463
	romreset			restore default romfile
	socket			display system socket information
	filter			
	ddns			
		debug	<level>	enable/disable ddns service
		display	<iface name>	display ddns information
		restart	<iface name>	restart ddns
		logout	<iface name>	logout ddns
	cpu			
		display		display CPU utilization
	xmodemmode	[crc checksum]		select xmodem mode

Exit Command

[home](#)

Command				Description
exit				exit smt menu

Ethernet Related Command

[home](#)

Command				Description
ether				
	config			display LAN configuration information
	driver			
		config	[0 1=auto normal] [0 1=10 100] [0 1=HD FD] <ch-name>	Configure LAN Settings Auto/Normal, 100/10 Mbps, Half/Full Duplex
		cnt		

		disp <name>	display ether driver counters
	status	<ch_name>	see LAN status
version			see ethernet device type
		packet <level>	set ether test packet display level
		event <ch> [on/off]	turn on/off ether test event display
	sap	[ch_name]	send sap packet
	arp	<ch_name> <ip-addr>	send arp packet to ip-addr
	disp	<ch_name>	display ethernet debug information
	level	<ch_name> <level>	set the ethernet debug level level 0: disable debug log level 1:enable debug log (default)

Wan Related Command

[home](#)

Command			Description	
Wan	adsl	Bert	ADSL ber	
		Chandata	ADSL channel data, line rate	
		close	Close ADSL line	
		Coding	ADSL standard current	
		Ctrleint	ADSL CTRLLE response command	
		Defbitmap	ADSL defect bitmap status	
		Dyinggasp	Send ADSL dyinggasp	
		Fwav	Test the ADSL F/W IO device is available or not	
		Fwdl	Download modem code, but must reset first	
		Linedata		
		Linedata	near	Show ADSL near end noise margin
		Linedata	far	Show ADSL far end noise margin
		Open	Open ADSL line	
		opencmd	Open ADSL line with specific standard	
		Opmode	Show the operational mode	
		Perfdata	Show performance information,CRC,FEC, error seconds..	
		Rdata	[start] [length]	Read DSP CTRLLE registers 512 bytes
		Reset		Reset ADSL modem, and must reload the modem code again
		Selftest		
		Selftest	Long	ADSL long loop test
		Selftest	short	ADSL short loop test
		Status		ADSL status (ex: up, down or wait for init)
		Version		ADSL version information

		Vendorid		ADSL vendor information
		Utopia		Show ADSL utopia information
		Cellcnt		Show ADSL cell counter
		display		
		display	shutdown	Show the counter of rate adaptive mechanism happening
		display	rateup	Show real status that rate adaptive mechanism happened
		Rateadap	[on off]	Turn on/off rate adaptive mechanism
		Dumpcondition	[on off]	Turn on/off online debug information of rate adaptive mechanism
		Sampletime	[mins]	Tune the sample time of rate adaptive mechanism
		Noisegt	[dB]	if noise margin is 3db greater than before, and rate is worse than before, then system will do “L1 shutdown RA3”, default is 3db
		Noisemargin	[dB]	if noise margin is greater than this value, and rate is worse than before, then system will do “L1 shutdown RA3”, default is 8db
		persisttime	[time]	when the adaptive condition is matched system will continue to monitor the time period “persisttime” before doing “L1 shutdown RA3”, default is 30 seconds
		Timeinterval	[mins]	when “L1 shutdown RA3” is done twice, and still can’t reach the max rate which system recorded, it will delay a time period that the period base time is “timeinterval” before starting again. The time-based default is 2 hrs
		Defectcheck	[on off]	Turn on/off defect table checking, default is on
		Txgain	[value]	Set the CTRL register (0xc3), the value is from 0xfa to 0x06
		Targetnoise	[value]	Set the CTRL register (0xc4), the value is from 0xfa to 0x06
		Maxtonelimit	[value]	Set the CTRL register (0xc5), the value is from 0xfa to 0x06
		Rxgain	[value]	Set the CTRL register (0xc6), the value is from 0xfa to 0x06
		Txoutputpwr	[value]	Set the CTRL register (0xc7), the value is from 0xfa to 0x06

		Rxoutputpwr	[value]	Set the CTRL register (0xc8), the value is from 0xfa to 0x06
		maxoutputpwr	[value]	Set the CTRL register (0xc9), the value is from 0xfa to 0x06
		Errorsecond		
		Errorsecond	Switch [1 0]	Turn on/off error sending to DSLAM side
		Errorsecond	sendes	Send current error second information immediately
		Dygasprecover		
		Dygasprecover	Level [value]	By default is 100, after receiving 100 dying gasp system will reboot
		Dygasprecover	Active [on off]	Turn on/off this mechanism
		rsploss	[1 0]	Turn on means to response signal loss of CTRL immediately, default is off
wan	hwsar	Disp		Display hwsar packets incoming/outgoing information
		Clear		Clear hwsar packets information
wan	hwsar	wdata		Write data into CTRL registers
wan	hwsar	issem		Send a command into CTRL
wan	hwsar	Disp		Display hwsar packets incoming/outgoing information
wan	Hwsar	clear		Clear Hwsar packets counter
wan	Hwsar	Sendoam		Send OAM packets: <vpi> <vci> <f5> <end-to-end> <type:0(AIS) 1(RDI) 2(LoopBack)>
wan	atm	test	oam	Send OAM packets: <vpi> <vci> <f5> <end-to-end> <type:0(AIS) 1(RDI) 2(LoopBack)>

IP Related Command

[home](#)

Command				Description
ip				
	address		[addr]	display host ip address
	alias		<iface>	alias iface
	aliasdis		<0 1>	disable alias
	arp			
		status	<iface>	display ip arp status
	dhcp		<iface>	
		client		

			release	release DHCP client IP
			renew	renew DHCP client IP
		status	[option]	show dhcp status
	dns			
		query		
		stats		
	httpd			
	icmp			
		status		display icmp statistic counter
		discovery	<iface> [on off]	set icmp router discovery flag
	ifconfig		[iface] [ipaddr] [broadcast <addr> mtu <value> dynamic]	configure network interface
	ping		<hostid>	ping remote host
	route			
		status	[if]	display routing table
		add	<dest_addr default>[/<bits>] <gateway> [<metric>]	add route
		addiface	<dest_addr default>[/<bits>] <gateway> [<metric>]	add an entry to the routing table to iface
		addprivate	<dest_addr default>[/<bits>] <gateway> [<metric>]	add private route
		drop	<host addr> [/<bits>]	drop a route
	status			display ip statistic counters
	udp			
		status		display udp status
	rip			
	tcp			
		status	[tcb] [<interval>]	display TCP statistic counters
	tftp			
	xparent			
		join	<iface1> [<iface2>]	join iface2 to iface1 ipxparent group
		break	<iface>	break iface to leave ipxparent group
	tredir			
	igmp			
		debug	[level]	set igmp debug level
		forwardall	[on off]	turn on/off igmp forward to all interfaces flag
		querier	[on off]	turn on/off igmp stop query flag
		iface		

			<iface> group <i>tm</i> <timeout>	set igmp group timeout
			<iface> interval <interval>	set igmp query interval
			<iface> join <group>	join a group on iface
			<iface> leave <group>	leave a group on iface
			<iface> query	send query on iface
			<iface> <i>rsptime</i> [time]	set igmp response time
			<iface> start	turn on of igmp on iface
			<iface> stop	turn off of igmp on iface
			<iface> ttl <threshold>	set ttl threshold
			<iface> v1compat [on off]	turn on/off v1compat on iface
		robustness	<num>	set igmp robustness variable
		status		dump igmp status
	pr			

Bridge Related Command

[home](#)

Command			Description
bridge			
	cnt		related to bridge routing statistic table
		disp	display bridge route counter
		clear	clear bridge route counter
	stat		related to bridge packet statistic table
		disp	display bridge route packet counter
		clear	clear bridge route packet counter