

Prestige P650H-11 3.40(FR.1)C0 Standard Version Release Note

Date: August 1, 2002

Supported Platforms:

TOSHIBA TMPR39280F

Versions:

ZyNOS Version: V3.40(FR.1)C0 | 8/1/2002

Bootbase Version: V1.05 | 7/29/2002 11:53:18

Notes:

1. The P650H-11 (ADSL Router) is a small-office and home device that will allow a small LAN to access the Internet. By integrating ADSL, and NAT capability, P650H-11 provides not only the ease of installation and Internet access, but also the most completed security solution to protect your intranet and efficient network management for data traffic.
The P650H-11 provides four single auto-sensing, auto-detection 10/100BASE-T Ethernet ports for connection to the user's local network, and a single RJ-11 port for connection to ADSL line.

Main features:

- ADSL

- Support Multi-Mode standard (ANSI T1.413,Issue 2 ; G.dmt(G.992.1); G-lite(G992.2)).
- Auto-negotiating rate adaptation
- ADSL physical connection ATM AAL5 (ATM Adaptation Layer type 5)
- Support multi-protocol over AAL5 (RFC1483)
- Support PPP over ATM AAL5 (RFC2364)
- PPP over Ethernet support for DSL connection (RFC 2516)
- Support VC-based and LLC-based multiplexing
- F4/F5 OAM

- Hardware

- Four 10/100M Ethernet UTP ports for LAN connection
- Restore Factory Defaults/Reboot button

- Router

- NAT (includes multi-to-multi NAT) / SUA
- Packet Filter
- VPN (IPSec, PPTP, & L2TP) pass through support
- Port forwarding
- Embedded Web Configuration
- SNMP v1 & v2c with MIB II

2. The version of Alcatel modem code is 3.8.164

Modification/Bug fixes:

Modification in 3.40(FR.1)b2 (July 29, 2002)

1. [ENHANCEMENT] Boot module is upgraded to 1.05 , because the model name is changed
2. [ENHANCEMENT] Modify encapsulation pattern “PPP” to be “PPPoA” in SMT and also Web/Wizard setup
3. [BUG FIX] HTP bug that the LAN external test failure is fixed
4. [BUG FIX] In Web/GUI, the F/W upgrade doesn’t work in IE 5.0 version 3315

Modification in 3.40(FR.1)b1 (July 23, 2002)

1. [ENHANCEMENT] The model name in main menu should differentiate P650H-11 or P650H-13, but it’s related with boot module
2. [ENHANCEMENT] Merge IGMP proxy feature from P643. The router acts as IGMP proxy which sends the leave/join message in case it received, and won’t send query message and also won’t execute group timeout event
3. [ENHANCEMENT] The ADSL disconnecting should be done by defect bitmap checking that means the logs “L1 shutdown by nlos” will be logged when ADSL is disconnected
4. [BUG FIX] ATM Rx ISR should check bad packets like CRC or length error
5. [BUG FIX] In smt24.10 the default value of daylight saving should be 01-01 (mm-dd)
6. [BUG FIX] Reject a SYN-ACK packets which causes embedded server Telnet/FTP/HTTP failure
7. [BUG FIX] Plug and unplug will cause system ATM initial failure and exception error
8. [BUG FIX] System hang up if press enter key in SMT menu 3.2 quickly

Modification in 3.40(FR.0)b11 (June 3, 2002)

- 1.Add CI commands “ether spi set <page> <address> <length> <data>”, and “ether spi get <page> <address> <length>” for Broadcom chip BCM3525M but it’s for internal usage only

Modification in 3.40(FR.0)b10 (May27, 2002)

- 1.CPU clock is changed back to 100Mhz

Modification in 3.40(FR.0)b9 (May 10, 2002)

- 1.Replace three string API (strcpy, strlen, strcmp) from Green Hill Library
2. Use a ROM controller to protect system from exception errors, but it is only enabled when EngDebugFlag is 0

Modification in 3.40(FR.0)b8 (May 7, 2002)

- 1 Boot module is upgrade to version 1.04
1. CPU clock is down to 80Mhz, UART baud-rate and timer-based clock is modified

Modification in 3.40(FR.0)b7 (April 30, 2002)

1.In Web/GUI modify the security page to be individual selections for embedded servers

Modification in 3.40(FV.0)b3 (March 25, 2002)

- 1.modify CI command “ppp lcp echotime”, if the parameter could be “0” which means to stop sending lcp echo requests
- 2.merge Dying Gasp recovery from P650R-11. If Dying Gasp Interrupt is received more than 100 times (by default) system will reboot

Modification in 3.40(FV.0)b2 (Mar 8, 2002)

1. Add CI command “sys atsh”.
2. Modify the default rom file setting for menu 4 , VPI/VCI : 8/32, DHCP pool size is 32, Client start IP = 192.168.1.33, encapsulation method is RFC1483 / LLC
3. Telnet will default login to SMT menu.
4. Add sptgen.
5. Merge NAT fix for OH Phone from P643R.
6. Add PPPoA dial on demand.
7. Add PPP idle timeout in menu 11.
8. Add call filter in menu 11.5.
9. Add firmware upgrade and restore to default romfile page in web.
10. Add remote management in web.
11. Add dynamic DNS in web.

Fixes in 3.40(FR.0)b13(June 7, 2002)

1. SUA/NAT server set table is configured to 1-2000 port forwarding to LAN host, and if the first packet is ICMP ping , system will get hang-up
- 2.In smt12, smt12.1, smt12.3, smt24.2, smt24.3, if users input a number first, and then left key, SMT will get hang-up

Fixes in 3.40(FR.0)b12(June 5, 2002)

1. IGMP doesn't work
2. In ATM layer, the incoming stray packets will be treated as OAM packets, and causes exception error
3. "wan hwsar disp", "wan atm test oam" should open for end users

Fixes in 3.40(FR.0)b11(June 3, 2002)

1. In Web GUI, LAN subnet mask is changed, but it doesn't work when LAN Host tries to get IP address from DHCP server
2. In SPTGEN, configure encapsulation to be PPP , but it doesn't work
- 3.after using “atur” to upload F/W, system should reboot directly, but sometimes system gets hang-up
- 4.When encapsulation is PPP connecting and then change to PPPoE, system will get exception error

Fixes in 3.40(FR.0)b10 (May 27, 2002)

1. “EnetEncap” doesn’t work, while it’s configured dynamic IP and ADSL is disconnect and connect again

Fixes in 3.40(FR.0)b9 (May 10, 2002)

1. Exception bug, ATUC is in bridge mode, ATUR smt11.1 bridge = Yes, and then switch smt 11.1 to routing mode, then system will get exception errors (bcproute.c)
2. One command will cause exception “sys iface disp wanif0 10”

Fixes in 3.40(FR.0)b7 (April 30, 2002)

1. Prevent from SNMP incorrect content packets attacking
2. After FTP upload ROM-0, telnet into system will cause exception errors
3. In Web/GUI, configure PPPoE VC and then LLC again and again, system will cause exception errors
4. Enhance codes to prevent from exception errors (ppp_down(), adslcallhistory(), IfGetNumDialingChann(), var_ipAddrTran(), EmbeddedSvrCheck(), embeddedSvrCheckICMP(), udp_input(), EtherStatusPeriodicUpdate(), TosIpCreate(), Channeltmout(), LoadFrom_memMapTab(), DumpmemMapTab())

Fixes in 3.40(FR.0)b6 (April 2, 2002)

1. In Web GUI, in login page, sometimes user must input username/password many times
2. The version of Alcatel modem code is 3.8.164

Fixes in 3.40(FV.0)b5 (March 29, 2002)

1. Remote management doesn’t work when SMT menu 15.2.1 is configured a port 21 to LAN host
2. Time Server function doesn’t get the update time after system reboot

Fixes in 3.40(FV.0)b4 (March 26, 2002)

1. OhPhone call H.323 bug fixed
2. In SPTGEN, allow menu15.2.1 server port start and port end
3. In SPTGEN, system will get reboot “in timer.c” if the encapsulation is ENET_ENCAP

Fixes in 3.40(FV.0)b3 (March 25, 2002)

1. In SPTGEN, nailed-up connection always On after put rom-t file
2. In SPTGEN, dynamic IP assignment can’t be configured
3. In SMT menu 12, static IP route can't input number 10-16

Known bugs:

1. Manufactory Data in Bootbase

ZyNOS Version	:	V3.40 (FR.1) 8/1/2002 17:12:04
Bootbase Version	:	V1.05 7/29/2002 11:53:18
Vendor Name	:	ZyXEL Communications Corp.
Product Model	:	Prestige 650H-11
ZyNOS ROM address	:	bfc20000
System Type	:	6
MAC Address	:	00A0C5012345
Default Country Code	:	FF
Boot Module Debug Flag	:	01
RomFile Version	:	35
RomFile Checksum	:	7707
ZyNOS Checksum	:	bd43
SNMP MIB level & OID	:	060102030405060708091011121314151617181920
Main Feature Bits	:	86
Other Feature Bits	:	 8F 00 00 00 00 00 00 00-00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00-00 40 13 40 00 00

Default ROM File Value Setting

- Menu 1: General Setup

Menu 1 - General Setup
System Name= ?
Location=
Contact Person's Name=
Route IP= Yes
Bridge= No
Press ENTER to Confirm or ESC to Cancel:

- Menu 3 - Ethernet Setup

Menu 3 - Ethernet Setup
1. LAN Port Filter Setup
2. TCP/IP and DHCP Setup
5. Wireless LAN Setup
1. LAN Port Filter Setup
Enter Menu Selection Number:

- Menu 3.1 - LAN Port Filter Setup

Menu 3.1 - LAN Port Filter Setup
Input Filter Sets:
protocol filters=
device filters=
Output Filter Sets:
protocol filters=
device filters=
Press ENTER to Confirm or ESC to Cancel:

- **Menu 3.2 - TCP/IP and DHCP Ethernet Setup**

```
Menu 3.2 - TCP/IP and DHCP Ethernet Setup
```

```
DHCP Setup
```

```
DHCP= Server
Client IP Pool Starting Address= 192.168.1.33
Size of Client IP Pool= 32
Primary DNS Server= 0.0.0.0
Secondary DNS Server= 0.0.0.0
Remote DHCP Server= N/A
```

```
TCP/IP Setup:
```

```
IP Address= 192.168.1.1
IP Subnet Mask= 255.255.255.0
RIP Direction= Both
Version= RIP-1
Multicast= None
IP Policies=
Edit IP Alias= No
```

```
Press ENTER to Confirm or ESC to Cancel:
```

- **Menu 4 - Internet Access Setup**

```
Menu 4 - Internet Access Setup
```

```
ISP's Name= MyISP
Encapsulation= ENET ENCAP
Multiplexing= LLC-based
VPI #= 8
VCI #= 35
ATM QoS Type= UBR
Peak Cell Rate (PCR)= 0
Sustain Cell Rate (SCR)= 0
Maximum Burst Size (MBS)= 0
My Login= N/A
My Password= N/A
ENET ENCAP Gateway= N/A
IP Address Assignment= Dynamic
IP Address= N/A
Network Address Translation= SUA Only
Address Mapping Set= N/A
```

```
Press ENTER to Confirm or ESC to Cancel:
```

- **Menu 11 Remote Node Setup**

Menu 11 - Remote Node Setup	
1. MyISP (ISP, SUA)	
2. _____	
3. _____	
4. _____	
5. _____	
6. _____	
7. _____	
8. _____	
Enter Node # to Edit:	

- **Menu 11.1 Remote Node Profile**

Menu 11.1 - Remote Node Profile	
Rem Node Name= MyISP	Route= IP
Active= Yes	Bridge= No
Encapsulation= ENET ENCAP	Edit IP/Bridge= No
Multiplexing= LLC-based	Edit ATM Options= No
Service Name= N/A	
Incoming:	Telco Option:
Rem Login= N/A	Allocated Budget(min)= N/A
Rem Password= N/A	Period(hr)= N/A
Outgoing:	Schedule Sets= N/A
My Login= N/A	Nailed-Up Connection= N/A
My Password= N/A	Session Options:
Authen= N/A	Edit Filter Sets= No
	Idle Timeout(sec)= N/A
Press ENTER to Confirm or ESC to Cancel:	

- **Menu 11.3 Remote Node Network Layer Options**

Menu 11.3 - Remote Node Network Layer Options	
IP Options:	Bridge Options:
IP Address Assignment = Dynamic	Ethernet Addr Timeout(min)= N/A
Rem IP Addr = 0.0.0.0	
Rem Subnet Mask= 0.0.0.0	
My WAN Addr= N/A	
NAT= SUA Only	
Address Mapping Set= N/A	
Metric= 2	
Private= No	
RIP Direction= None	
Version= RIP-1	
Multicast= None	
IP Policies=	
Enter here to CONFIRM or ESC to CANCEL:	

- Menu 11.5 Remote Node Filter

Menu 11.5 - Remote Node Filter

Input Filter Sets:
 protocol filters= 12, 11
 device filters=
 Output Filter Sets:
 protocol filters=
 device filters=

Enter here to CONFIRM or ESC to CANCEL:

- Menu 11.6 - Remote Node ATM Layer Options

Menu 11.6 - Remote Node ATM Layer Options

VPI/VCI (LLC-Multiplexing or PPP-Encapsulation)

VPI #= 8
 VCI #= 35
 ATM QoS Type= UBR
 Peak Cell Rate (PCR)= 0
 Sustain Cell Rate (SCR)= 0
 Maximum Burst Size (MBS)= 0

Enter here to CONFIRM or ESC to CANCEL:

- Menu 12 - Static Route Setup

Menu 12 - Static Route Setup

1. IP Static Route
3. Bridge Static Route

Please enter selection:

- Menu 12.1 IP Static Route Setup

Menu 12.1 - IP Static Route Setup

1. _____
2. _____
3. _____
4. _____
5. _____
6. _____
7. _____
8. _____
9. _____
10. _____
11. _____
12. _____
13. _____
14. _____
15. _____
16. _____

Enter selection number:

- Menu 12.3 Bridge Static Route Setup

Menu 12.3 - Bridge Static Route Setup

1. _____
2. _____
3. _____
4. _____

Enter selection number:

- Menu 15 - NAT Setup

Menu 15 - NAT Setup

1. Address Mapping Sets
2. NAT Server Sets

Enter Menu Selection Number:

- Menu 15.1 - Address Mapping Sets

Menu 15.1 - Address Mapping Sets

1.
2.
3.
4.
5.
6.
7.
8.
255. SUA (read only)

Enter Menu Selection Number:

- Menu 15.2 - NAT Server Sets

Menu 15.2 - NAT Server Sets

1. Server Set 1 (Used for SUA Only)
2. Server Set 2
3. Server Set 3
4. Server Set 4
5. Server Set 5
6. Server Set 6
7. Server Set 7
8. Server Set 8
9. Server Set 9
10. Server Set 10

Enter Set Number to Edit:

- **Menu 15.2.1 - NAT Server Setup (Used for SUA Only)**

Menu 15.2.1 - NAT Server Setup (Used for SUA Only)			
Rule	Start Port No.	End Port No.	IP Address
1.	Default	Default	0.0.0.0
2.	0	0	0.0.0.0
3.	0	0	0.0.0.0
4.	0	0	0.0.0.0
5.	0	0	0.0.0.0
6.	0	0	0.0.0.0
7.	0	0	0.0.0.0
8.	0	0	0.0.0.0
9.	0	0	0.0.0.0
10.	0	0	0.0.0.0
11.	0	0	0.0.0.0
12.	0	0	0.0.0.0

Press ENTER to Confirm or ESC to Cancel:

- **Menu 21 Filter Set Configuration**

Menu 21 - Filter Set Configuration			
Filter Set #	Comments	Filter Set #	Comments
1	_____	7	_____
2	NetBIOS_WAN	8	_____
3	NetBIOS_LAN	9	_____
4	_____	10	_____
5	_____	11	WebSet1
6	_____	12	WebSet2

Enter Filter Set Number to Configure= 0

Edit Comments= N/A

Press ENTER to Confirm or ESC to Cancel:

- **Menu 21.2 Filter Rules Summary**

Menu 21.2 - Filter Rules Summary				
#	A	Type	Filter Rules	M m n
1	Y	IP	Pr=6, SA=0.0.0.0, DA=0.0.0.0, DP=137	N D N
2	Y	IP	Pr=6, SA=0.0.0.0, DA=0.0.0.0, DP=138	N D N
3	Y	IP	Pr=6, SA=0.0.0.0, DA=0.0.0.0, DP=139	N D N
4	Y	IP	Pr=17, SA=0.0.0.0, DA=0.0.0.0, DP=137	N D N
5	Y	IP	Pr=17, SA=0.0.0.0, DA=0.0.0.0, DP=138	N D N
6	Y	IP	Pr=17, SA=0.0.0.0, DA=0.0.0.0, DP=139	N D F

- Menu 21.3 Filter Rules Summary

Menu 21.3 - Filter Rules Summary			
#	A Type	Filter Rules	M m n
-	-	-	-
1	Y IP	Pr=17, SA=0.0.0.0, SP=137, DA=0.0.0.0, DP=53	N D F
2	N		
3	N		
4	N		
5	N		
6	N		

- Menu 21.11 Filter Rules Summary

Menu 21.11 - Filter Rules Summary			
#	A Type	Filter Rules	M m n
-	-	-	-
1	Y IP	Pr=17, SA=0.0.0.0, DA=0.0.0.0, DP=161	N D N
2	Y IP	Pr=17, SA=0.0.0.0, DA=0.0.0.0, DP=162	N D F
3	N		
4	N		
5	N		
6	N		

- Menu 21.12 Filter Rules Summary

Menu 21.12 - Filter Rules Summary			
#	A Type	Filter Rules	M m n
-	-	-	-
1	Y IP	Pr=6, SA=0.0.0.0, DA=0.0.0.0, DP=23	N D N
2	Y IP	Pr=6, SA=0.0.0.0, DA=0.0.0.0, DP=21	N D N
3	Y IP	Pr=17, SA=0.0.0.0, DA=0.0.0.0, DP=69	N D N
4	Y IP	Pr=6, SA=0.0.0.0, DA=0.0.0.0, DP=80	N D N
5	N		
6	N		

- Menu 22 - SNMP Configuration:

Menu 22 - SNMP Configuration	
SNMP:	
Get Community=	public
Set Community=	public
Trusted Host=	0.0.0.0
Trap:	
Community=	public
Destination=	0.0.0.0
Press ENTER to Confirm or ESC to Cancel:	

- **Menu 23 – System Password:**

Menu 23 - System Password

Old Password= ?
New Password= ?
Retype to confirm= ?

Enter here to CONFIRM or ESC to CANCEL:

- **Menu 24.2.2: System Maintenance – Change Console Port Speed**

Menu 24.2.2 - System Maintenance - Change Console Port Speed

Console Port Speed: 9600

Press ENTER to Confirm or ESC to Cancel:

- **Menu 24.3: System Maintenance – UNIX Syslog**

Menu 24.3.2 - System Maintenance - UNIX Syslog

UNIX Syslog:
Active= No
Syslog IP Address= ?
Log Facility= Local 1

Types:
CDR= No
Packet triggered= No
Filter log= No
PPP log= No

Press ENTER to Confirm or ESC to Cancel:

- **Menu 24.10: System Maintenance – Time and Date Setting**

Menu 24.10 - System Maintenance - Time and Date Setting

Use Time Server when Bootup= None
Time Server Address= N/A

Current Time: 00 : 12 : 37
New Time (hh:mm:ss): 00 : 12 : 33

Current Date: 2000 - 01 - 01
New Date (yyyy-mm-dd): 2000 - 01 - 01

Time Zone= GMT

Daylight Saving= No
Start Date (mm-dd): 01 - 01
End Date (mm-dd): 01 - 01

Press ENTER to Confirm or ESC to Cancel:

- Menu 24.11: Remote Management -- Remote Management Control

Menu 24.11 - Remote Management Control		
TELNET Server:		
Server Port = 23	Server Access = ALL	
Secured Client IP = 0.0.0.0		
FTP Server:		
Server Port = 21	Server Access = ALL	
Secured Client IP = 0.0.0.0		
Web Server:		
Server Port = 80	Server Access = ALL	
Secured Client IP = 0.0.0.0		
Press ENTER to Confirm or ESC to Cancel:		

- Menu 25 - IP Routing Policy Setup

Menu 25 - IP Routing Policy Setup			
Policy Set #	Name	Policy Set #	
-----	-----	-----	
1	_____	7	_____
2	_____	8	_____
3	_____	9	_____
4	_____	10	_____
5	_____	11	_____
6	_____	12	_____
Enter Policy Set Number to Configure= 0			
Edit Name= N/A			
Press ENTER to Confirm or ESC to Cancel:			

- Menu 26 - Schedule Setup

Menu 26 - Schedule Setup			
Schedule Set #	Name	Schedule Set #	
-----	-----	-----	
1	AlwaysOn	7	_____
2	_____	8	_____
3	_____	9	_____
4	_____	10	_____
5	_____	11	_____
6	_____	12	_____
Enter Schedule Set Number to Configure= 0			
Edit Name= N/A			
Press ENTER to Confirm or ESC to Cancel:n			

- Menu 26.1 - Schedule Setup

```

      Menu 26.1 Schedule Set Setup

Active= Yes
Start Date(yyyy-mm-dd)= 2000 - 01 - 01
How Often= Weekly
Once:
Date (yyyy-mm-dd)= N/A
Weekdays:
Sunday= Yes
Monday= Yes
Tuesday= Yes
Wednesday= Yes
Thursday= Yes
Friday= Yes
Saturday= Yes
Start Time(hh:mm)= 00 : 00
Duration(hh:mm)= 23 : 59
Action= Forced On

Press ENTER to Confirm or ESC to Cancel:n

```

- ras> sys view autoexec.net
 - ppp ipcp compress off
 - sys wdog sw on
 - sys errctl 0
 - sys trcl level 5
 - sys trcl type 1180
 - sys trcp cr 64 96
 - sys trcl sw off
 - sys trcp sw off
 - ip tcp mss 512
 - ip tcp limit 2
 - ip tcp irtt 65000
 - ip tcp window 2
 - ip tcp ceiling 6000
 - ip rip activate
 - ip rip merge on
 - ip icmp discovery enif0 off
 - sys quick enable
 - wan adsl rate off