



Firmware Release Note

Prestige 650HW-31

Standard version

Release 3.40(IS.0)C0

Date:

Dec. 19, 2002

Author:

Brian Chung

ZyXEL Prestige 650HW-31 Standard Version release 3.40(IS.0)C0 Release Note

Date: Dec. 19, 2002

Supported Platforms:

ZyXEL Prestige 650HW-31

Versions:

ZyNOS F/W Version : V3.40(IS.0) | 12/19/2002 16:03:42

BootBase : V1.05 | 11/4/2002 15:24:43

Notes:

The P650HW-31 is a small-office and home device that will allow a small LAN to access the Internet. By integrating ADSL, WLAN, NAT, P650HW-31 provides the ease of installation and Internet access.

The P650HW-31 provides an PCMCIA wireless card slot for 802.11b Wireless LAN connectivity, four single auto-sensing, auto-detection 10/100BASE-T Ethernet ports for connection to the user's local network, and a single RJ-11 port for connection to ADSL line.

The version of Alcatel modem code is 3.9.122

Known Issues:

Features:

Modifications in V 3.40(IS.0)b5 | 12/5/2002

1. [BUG FIXED]
Sympton: When system reboot, sometimes exception occurred.
Condition: While ADSL initializing, reboot the system, then exception occurred.
2. [BUG FIXED]
Sympton: FTP uploading, there are many ping timeout.
Condition: When traffic is upstream direction, there are many ping timeout.
3. [BUG FIXED]
Sympton: HTP fail at AT commond "ATTI" test.
Condition: While doing ATTI HTP test, LAN Internal test will fail.
4. [BUG FIXED]

Sympton: WLAN LED status error.

Condition: While WLAN stop send/receive, the WALN LED still blinking.

5. [FEATURE ENHANCED]

Sympton: Adopt new compress algorithm to reduce firmware size.

6. [BUG FIXED]

Sympton: There is downstream cell loss under 64, 128, 256 frame size.

Condition: Connect to AX4000 with Alcatel DSLAM for testing cell loss.

7. [BUG FIXED]

Sympton: In menu 24.1, the status of Ethernet always display “100M/Full Duplex”.

Modifications in V 3.40(IS.0)b4 | 12/2/2002

1. Hardware Test Program ready.

Modifications in V 3.40(IS.0)b3 | 11/22/2002

1. WLAN and LED ready.

Modifications in V 3.40(IS.0)b2 | 11/13/2002

1. Hub feature ready.

Modifications in V 3.40(IS.0)b1 | 11/11/2002

1. Create this project.

Annex A CI Command List

Command Class List Table		
System Related Command	Exit Command	Device Related Command
Ethernet Related Command	POE Related Command	IP Related Command
PPP Related Command	Bridge Related Command	HDAP Related Command
WLAN Related Command		

System Related Command

[Home](#)

Command				Description
sys				
	adjtime			retrive date and time from Internet
	cbuf			
		Display	[a f u]	display cbuf a: all f: free u: used
		Cnt		cbuf static
			Display	display cbuf static
			Clear	clear cbuf static
	baud		<1..5>	change console speed
	callhist			
		add	<phone dir [rate] [upTime]>	add entry to call history
		display		display call history
		remove	<index>	remove entry from call history
	clear			clear the counters in GUI status menu
	clock			
		display		display system clock
	countrycode		[countrycode]	set country code
	date		[year month date]	set/display date
	dir			display file directory
	domainname			display domain name
	edit		<filename>	edit a text file
	enhanced			return OK if commands are supported for PWC purposes
	errctl		[level]	set the error control level 0:crash no save,not in debug mode (default) 1:crash no save,in debug mode 2:crash save,not in debug mode 3:crash save,in debug mode
	event			
		display		display tag flags information
		trace		display system event information
			display	display trace event
			clear <num>	clear trace event
	extraphnum			maintain extra phone numbers for outcalls
		add	<set 1-3> <1st phone num> [2nd phone num]	add extra phone numbers
		display		display extra phone numbers
		node	<num>	set all extend phone number to remote node <num>
		remove	<set 1-3>	remove extra phone numbers
		reset		reset flag and mask
	feature			display feature bit
	fid			

		display		display function id list
	firmware			display ISDN firmware type
	hostname		[hostname]	display system hostname
	iface			
		disp	[#]	display iface list
	isr		[all used free]	display interrupt service routine
	interrupt			display interrupt status
	log			
		category		
			access [0:none/1:log]	record the access control logs
			attack [0:none/1:log/2:alert/3:both]	record and alert the firewall attack logs
			display	display the category setting
			error [0:none/1:log/2:alert/3:both]	record and alert the system error logs
			ipsec [0:none/1:log]	record the access control logs
			javablocked [0:none/1:log]	record the java etc. blocked logs
			mten [0:none/1:log]	record the system maintenance logs
			upnp [0:none/1:log]	record upnp logs
			urlblocked [0:none/1:log/2:alert/3:both]	record and alert the web blocked logs
			urlforward [0:none/1:log]	record web forward logs
		clear		clear log
		display		display all logs
		errlog		
			clear	display log error
			disp	clear log error
			online	turn on/off error log online display
		load		load the log setting buffer
		mail		
			alertAddr [mail address]	send alerts to this mail address
			display	display mail setting
			logAddr [mail address]	send logs to this mail address
			schedule display	display mail schedule
			schedule hour [0-23]	hour time to send the logs
			schedule minute [0-59]	minute time to send the logs
			schedule policy [0:full/1:hourly/2:daily/3:weekly/4:none]	mail schedule policy
			schedule week [0:sun/1:mon/2:tue/3:wed/4:thu/5:fri/6:sat]	weekly time to send the logs
			server [domainName/IP]	mail server to send the logs
			subject [mail subject]	mail subject
		save		save the log setting buffer
		syslog		
			active [0:no/1:yes]	active to enable unix syslog
			display	display syslog setting
			facility [Local ID(1-7)]	log the messages to different files
			server [domainName/IP]	syslog server to send the logs
	log			
		clear		clear log error
		disp		display log error
		online	[on/off]	turn on/off error log online display
	map			display whole memory map content
	mbuf			

		link	link	list system mbuf link
		pool	<id> [type]	list system mbuf pool
		status		display system mbuf status
		disp	<address>	display mbuf status
		cnt		
			disp	display system mbuf count
			clear	clear system mbuf count
		debug	[on off]	
	memory		<address> <length>	display memory content
	memwrite		<address> <len> [data list ...]	write some data to memory at <address>
	memwl		<address>	write long word to memory at <address>
	memrl		<address>	read long word at <address>
	memutil			
		usage		display memory allocate and heap status
		mqueue	<address> <len>	display memory queues
		mcell	mid [f u]	display memory cells by given ID
		msecs	[a f u]	display memory sections
		mtstart	<n-mcell>	start memory test
		mtstop		stop memory test
		mtalloc	<size> [n-mcell]	allocate memory for testing
		mtfree	<start-idx> [end-idx]	free the test memory
	model			display server model name
	proc			
		display		display all process information
		stack	[tag]	display process's stack by a give TAG
		pstatus		display process's status by a give TAG
	pwc			sends information to PWC via telnet
	queue			
		display	[a f u] [start#] [end#]	display queue by given status and range numbers
		ndisp	[qid]	display a queue by a given number
	quit			quit CI command mode
	reboot		[code]	reboot system code = 0 cold boot, = 1 immediately boot = 2 bootModule debug mode
	reslog			
		disp		display resources trace
		clear		clear resources trace
	stdio		[second]	change terminal timeout value
	time		[hour [min [sec]]]	display/set system time
	timer			
		disp		display timer cell
		trace	[on off]	set/display timer information online
		start	[tmValue]	start a timer
		stop	<ID>	stop a timer
	trcdisp			monitor packets
	trclog			
		switch	[on off]	set system trace log
		online	[on off]	set on/off trace log online
		level	[level]	set trace level of trace log #:1-10
		type	<bitmap>	set trace type of trace log
		disp		display trace log
		clear		clear trace

		call		display call event
		encapmask	[mask]	set/display tracelog encapsulation mask
	trcpacket			
		create	<entry> <size>	create packet trace buffer
		destroy		packet trace related commands
		channel	<name> [none incoming outgoing bothway]	<channel name>=enet0,sdsl00, fr0 set packet trace direction for a given channel
		string		enable smt trace log
		switch	[on/off]	turn on/off the packet trace
		disp		display packet trace
		udp		send packet trace to other system
			switch [on/off]	set tracepacket upd switch
			addr <addr>	send trace packet to remote udp address
			port <port>	set tracepacket udp port
		parse	[[start_idx], end_idx]	parse packet content
		brief		display packet content briefly
	syslog			
		server	[destIP]	set syslog server IP address
		facility	<FacilityNo>	set syslog facility
		type	[type]	set/display syslog type flag
		mode	[on/off]	set syslog mode
	version			display RAS code and driver version
	view		<filename>	view a text file
	wdog			
		switch	[on/off]	set on/off wdog
		cnt	[value]	display watchdog counts value: 0-34463
		dead		let watch dog take place using while loop
	romreset			restore default romfile
	server			
		access	<telnet ftp web icmp snmp dns> <value>	set server access type
		load		load server information
		disp		display server information
		port	<telnet ftp web snmp> <port>	set server port
		save		save server information
		secureip	<telnet ftp web icmp snmp dns> <ip>	set server secure ip addr
	spt			
		dump		dump spt raw data
			root	dump spt root data
			rn	dump spt remote node data
			user	dump spt user data
			slot	dump spt slot data
		set	<offset> <len> <value...>	set spt value in memory address
		save		save spt data
		size		display spt record size
		clear		clear spt data
	cmgr			
		trace		
			disp <ch-name>	show the connection trace of this channel
			clear <ch-name>	clear the connection trace of this channel
		data	<ch-name>	show channel connection related data
		cnt	<ch-name>	show channel connection related counter
	socket			display system socket information
	filter			

		clear		clear filter statistic counter
		disp		display filter statistic counters
		sw	[on off]	set filter status switch
		rule	<iface>	display iface filter flag
		set	<set>	display filter rule
		addNetBios		add netbios filter
		removeNetBios		remove netbios filter
		netbios		
			disp	display netbios filter status
			config <0:LAN to WAN, 1:WAN to LAN, 2:LAN to DMZ, 3:IPSec passthrough, 4:Trigger Dial> <on off>	config netbios filter
		blockbc	[on off]	set/display broadcast filter mode
	ddns			
		debug	<level>	enable/disable ddns service
		display	<iface name>	display ddns information
		restart	<iface name>	restart ddns
		logout	<iface name>	logout ddns
	cpu			
		display		display CPU utilization

Exit Command

[Home](#)

Command				Description
exit				exit smt menu

Device Related Command

[Home](#)

Command				Description
dev				
	channel			
		Name	<all use>	list channel name
		Drop	<channel name>	drop channel
		Disp	<channel name> [level]	display channel
		Threshold	<channel name> [number]	set channel threshold
	dial		<node#>	dial to remote node

Ethernet Related Command

[Home](#)

Command				Description
ether				
	config			display LAN configuration information
	driver			
		Cnt		
			disp <name>	display ether driver counters
			clear <name>	clear ether driver counters
		Iface	<ch_name> <num>	send driver iface
		Ioctl	<ch_name>	Useless in this stage.
		Mac	<ch_name> <mac_addr>	Set LAN Mac address
		Reg	<ch_name>	display LAN hardware related registers
		Rxmod	<ch_name> <mode>	set LAN receive mode. mode: 1: turn off receiving 2: receive only packets of this interface 3: mode 2+ broadcast 5: mode 2 + multicast 6: all packets
		Status	<ch_name>	see LAN status

	Init	<ch_name>	initialize LAN
version			see ethernet device type
pkttest			
	Disp		
		packet <level>	set ether test packet display level
		event <ch> [on/off]	turn on/off ether test event display
	Sap	[ch_name]	send sap packet
	Arp	<ch_name> <ip-addr>	send arp packet to ip-addr
	Mem	<addr> <data> [type]	write memory data in address
test		<ch_id> <test_id> [arg3] [arg4]	do LAN test
pncconfig		<ch_name>	do pnc config
mac		<src_ch> <dest_ch> <ipaddr>	fake mac address

POE Related Command

[Home](#)

Command				Description
poe				
	debug		[on/off]	switch poe debug
	retry			
		count	[count]	set/display poe retry count
		interval	[interval]	set/display poe retry interval
	status		[ch_name]	see poe status
	master			
		promiscuous	[on/off]	provide pppoe server list to client
		easy	[on/off]	response for no service name request
	service			
		add	<service-name>	add poe service
		show		show poe service
	dial		<node>	dial a remote node
	drop		<node>	drop a pppoe call
	channel			
		enable	<channel>	enable a channel to carry pppoe traffic
		disable	<channel>	disable a pppoe channel
		show		show pppoe channel
	padt		[limit]	set/display pppoe PADT limit
	inout		<node name>	set call direction to both
	ippool		[ip] [cnt]	set/display pppoe ippool information

IP Related Command

[Home](#)

Command				Description
ip				
	address		[addr]	display host ip address
	alias		<iface>	alias iface
	aliasdis		<0 1>	disable alias
	arp			
		status	<iface>	display ip arp status
		add	<hostid> ether <ether addr>	add arp information
		resolve	<hostid>	resolve ip-addr
		replydif	[<0:No 1:yes>]	reply different interface ip-addr's arp request
		drop	<hostid> [hardware]	drop arp
		flush		flush arp table
		publish		add proxy arp
	dhcp		<iface>	
		client		
		release		release DHCP client IP

		renew	renew DHCP client IP
	mode	<server relay none client>	set dhcp mode
	relay	server <serverIP>	set dhcp relay server ip-addr
	reset		reset dhcp table
	server		
		probecount <num>	set dhcp probe count
		dnsserver <IP1> [IP2] [IP3]	set dns server ip-addr
		winsserver <winsIP1> [<winsIP2>]	set wins server ip-addr
		gateway <gatewayIP>	set gateway
		hostname <hostname>	set hostname
		initialize	fills in DHCP parameters and initializes (for PWC purposes)
		leasetime <period>	set dhcp leasetime
		netmask <netmask>	set dhcp netmask
		pool <startIP> <numIP>	set dhcp ip pool
		renewaltime <period>	set dhcp renew time
		rebindtime <period>	set dhcp rebind time
		reset	reset dhcp table
		server <serverIP>	set dhcp server ip for relay
		dnsorder [router isp]	set dhcp dns order
	status	[option]	show dhcp status
	static		
		delete <num> all	delete static dhcp mac table
		display	display static dhcp mac table
		update <num> <mac> <ip>	update static dhcp mac table
dns			
	query		
		address <ipaddr> [timeout]	resolve ip-addr to name
		debug <num>	enable dns debug value
		name <hostname> [timeout]	resolve name to ip-addr
		status	display dns query status
		table	display dns query table
	server	<primary> [secondary] [third]	set dns server
	stats		
		clear	clear dns statistics
		disp	display dns statistics
	table		display dns table
httpd			
	debug	[on off]	set http debug flag
icmp			
	echo	[on off]	set icmp echo response flag
	data	<option>	select general data type
	check		
		cmd [on off]	check icmp echo reply command data
		rsp [on off]	check icmp response
		indication [i r l p]	set icmp indication
	status		display icmp statistic counter
	trace	[on off]	turn on/off trace for debugging
	discovery	<iface> [on off]	set icmp router discovery flag
ifconfig		[iface] [ipaddr] [broadcast <addr> mtu <value> dynamic]	configure network interface
ifdrop		<iface>	check if iface is available.
ping		<hostid>	ping remote host

	pong		<hostid> [<size> <time-interval>]	pong remote host
	route			
		status	[if]	display routing table
		add	<dest_addr default>[/<bits>] <gateway> [<metric>]	add route
		addiface	<dest_addr default>[/<bits>] <gateway> [<metric>]	add an entry to the routing table to iface
		addprivate	<dest_addr default>[/<bits>] <gateway> [<metric>]	add private route
		drop	<host addr> [/<bits>]	drop a route
		flush		flush route table
		lookup	<addr>	find a route to the destination
		errcnt		
			disp	display routing statistic counters
			clear	clear routing statistic counters
	status			display ip statistic counters
	adjTcp		<iface> [<mss>]	adjust the TCP mss of iface
	udp			
		status		display udp status
	rip			
		accept	<gateway>	drop an entry from the RIP refuse list
		activate		enable rip
		merge	[on/off]	set RIP merge flag
		refuse	<gateway>	add an entry to the rip refuse list
		request	<addr> [port]	send rip request to some address and port
		reverse	[on/off]	RIP Poisoned Reverse
		status		display rip statistic counters
		trace		enable debug rip trace
		mode		
			<iface> in [mode]	set rip in mode
			<iface> out [mode]	set rip out mode
		dialin_user	[show in out both none]	show dialin user rip direction
	tcp			
		ceiling	[value]	TCP maximum round trip time
		floor	[value]	TCP minimum rtt
		irtt	[value]	TCP default init rtt
		kick	<tcb>	kick tcb
		limit	[value]	set tcp output window limit
		max-incomplete	[number]	Set the maximum number of TCP incomplete connection.
		mss	[value]	TCP input MSS
		reset	<tcb>	reset tcb
		rtt	<tcb> <value>	set round trip time for tcb
		status	[tcb] [<interval>]	display TCP statistic counters
		syndata	[on/off]	TCP syndata piggyback
		trace	[on/off]	turn on/off trace for debugging
		window	[tcb]	TCP input window size
	samenet		<iface1> [<iface2>]	display the ifaces that in the same net
	uninet		<iface>	set the iface to uninnet
	tftp			
		support		prtn if tftp is support
		stats		display tftp status
	xparent			
		join	<iface1> [<iface2>]	join iface2 to iface1 group

		break	<iface>	break iface to leave ipxparent group
	aniprobe		<0 1> 1:yes 0:no	set ip anti-probe flag
	igmp			
		debug	[level]	set igmp debug level
		forwardall	[on off]	turn on/off igmp forward to all interfaces flag
		querier	[on off]	turn on/off igmp stop query flag
		iface		
			<iface> grouptm <timeout>	set igmp group timeout
			<iface> interval <interval>	set igmp query interval
			<iface> join <group>	join a group on iface
			<iface> leave <group>	leave a group on iface
			<iface> query	send query on iface
			<iface> rsptime [time]	set igmp response time
			<iface> start	turn on of igmp on iface
			<iface> stop	turn off of igmp on iface
			<iface> ttl <threshold>	set ttl threshold
			<iface> v1compat [on off]	turn on/off v1compat on iface
		robustness	<num>	set igmp robustness variable
		status		dump igmp status
	pr			
		clear		clear ip pr table counter information
		disp		dump ip pr table counter information
		switch		turn on/off ip pr table counter flag
	nat			
		debug	[on off]	turn on/off the nat debug flag
		period	[period]	set nat timer period
		port	[port]	set nat starting external port number
		checkport		verify all server tables are valid
		timeout		
			gre [timeout]	set nat gre timeout value
			iamt [timeout]	set nat iamt timeout value
			generic [timeout]	set nat generic timeout value
			reset [timeout]	set nat reset timeout value
			tcp [timeout]	set nat tcp timeout value
			tcpother [timeout]	set nat tcp other timeout value
		update		create nat system information from spSysParam
		iamt		display nat iamt information
		iface	<iface>	show nat status of an interface
		lookup	<rule set>	display nat lookup rule
		new-lookup	<rule set>	display new nat lookup rule
		loopback	[on off]	turn on/off nat loopback flag
		reset	<iface>	reset nat table of an iface
		server		
			disp	display nat server table
			load <set id>	load nat server information from ROM
			save	save nat server information to ROM
			clear <set id>	clear nat server information
			edit active <yes no>	set nat server edit active flag
			edit svrport <start port> [end port]	set nat server server port
			edit intport <start port> [end port]	set nat server forward port
			edit remotehost <start ip> [end ip]	set nat server remote host ip
			edit leasetime [time]	set nat server lease time
			edit rulename [name]	set nat server rule name
			edit forwardip [ip]	set nat server server ip

		edit protocol [protocol id]	set nat server protocol
	service		
		irc [on off]	turn on/off irc flag
	resetport		reset all nat server table entries
	incikeport	[on off]	turn on/off increase ike port flag

PPP Related Command

[Home](#)

Command				Description
ppp				
	bod			
		remote	<iface>	show remote bod information
		reset		reset bod
		setremote	<iface>	set remote bod
		status	<wan_iface>	show wan port bod status
		clear	<wan_iface>	clear wan port bod data
		on		set bod flag on
		off		set bod flag off
		node	<node> <dir>	config the statistic method for remote node bod traffic data
		debug	[on off]	show bod debug flag
		cnt		
			disp	show bod state
			clear	clear bod state
	ccp		[on off]	set/display dial-in ccp switch
	lcp			
		acfc	[on off]	set address/control field compression flag
		pfc	[on off]	set protocol field compression flag
		mpin	[on off]	set incoming call MP flag
		callback	[on off]	set callback flag
		bacp	[on off]	set bandwidth allocation control flag
		echo		
			retry <retry_count>	set/display retry count to send echo-request
			time <interval>	set/display time interval to send echo-request
	ipcp			
		close		close connection on ppp interface
		list	<iface>	show ipcp state
		open		open fsm link
		timeout	[value]	set timeout interval when waiting for response from remote peer
		try		
			configure [value]	set/display fsm try config
			failure [value]	set/display fsm try failure
			terminate [value]	set/display fsm try terminate
		compress	[on off]	set compress flag
		slots	[slot_num]	set number of slots
		idcompress	[on off]	set/display slot id compress
		address	[on off]	set/display ip one address option
	mp			
		default		show link default flag
			rotate	set link default to rotate
			split	set link default to split
		split	[0 1]	set/display link split
		rotate	[0 1]	set/display link rotate

		sequence		set/display mp start sequence
	configure			
		ipcp		
			compress [on/off]	enable/disable compress
			slots [slot_num]	select number of slots
			idcompress [on/off]	enable/disable slot id compress
			address [on/off]	set/display ip one address option
		atcp		apple talk feature not supported anymore
		ccp		
			ascend [on/off]	set/display ascend stac flag
			history <count>	set/display stac history count
			check [argv]	set/display stac check mode
			reset <mode>	set/display stac reset mode
			pfc [on/off]	set/display pfc flag
			debug [on/off]	set/display ccp debug flag
	iface			
			<iface> ipcp	show the ipcp status of the given iface
			<iface> ipxcp	show the ipxcp status of the given iface
			<iface> atcp	
			<iface> ccp [reset skip flush]	show the ccp status of the given iface
			<iface> mp	show the mp status of the given iface
	show		<channel>	show the ppp channel status
	fsm			
		trace		
			break [num] [count] [flag]	set the fsm log break value
			clear	clear the fsm log data
			disp	display the fsm log data
			filter [mask] [protocol]	set the fsm log filter value
		Tdata		
			filter [protocol1] [protocol2] ...	set the fsm filter data
			disp	display the fsm data
			clear	clear the fsm data
		Struc		dump fsm data structure
	delay		[interval]	set the delay timer for sending first PPP packet after call answered

Bridge Related Command[Home](#)

Command				Description
bridge				
	mode		<1/0> (enable/disable)	turn on/off (1/0) LAN promiscuous mode
	blt			related to bridge local table
		Disp	<channel>	display blt data
		reset	<channel>	reset blt data
		traffic		display local LAN traffic table
		monitor	[on/off]	turn on/off traffic monitor. Default is off.
		Time	<sec>	set blt re-init interval
	brt			related to bridge route table
		Disp	[id]	display brt data
		reset	[id]	reset brt data
	cnt			related to bridge routing statistic table
		Disp		display bridge route counter
		clear		clear bridge route counter
	stat			related to bridge packet statistic table
		Disp		display bridge route packet counter

		clear		clear bridge route packet counter
	Disp			display bridge source table

HDAP Related Command

[Home](#)

Command				Description
hdap				
	Debug		[on/off]	set hdap debug flag
	Reset			reset hdap

WLAN Related Command

[Home](#)

Command				Description
Wlan				
	Essid			Configure ESSID
	Chid			Configure channel ID
	debug			Turn on /off debug information
	version			Show WLAN AP F/W version